

TRUST YOUR EARS!

NEW PRODUCTS 2018





COMPACT COAXIAL FULLRANGE SPEAKER




- **PRESENTATION**
- Very compact and powerful fullrange speaker
- ► 6,5" / 1" neodymium coax
- ► Controled 70° conical dispersion pattern
- ▶ 123 dB Max SPL
- ➤ 300W cont. power handling
- ▶ 8 ohm input with deticated passive crossover network
- Avaliable with speakon connectors for tour and portable use
- Avaliable with Phoenix connectors for installing
- Smart quick-set hardware for adjusting dispersion angle 0° 360°
- Bracket for installing or for use on speaker stand, microphone stand and wall mount.

DESIGNED FOR

- The rental and event industry
- Installations in theatres, conference, restaurants and bars, lounges and hotels
- Presentations, recorded music, live performance, speech
- Front-fill
- In-fill
- Delay speaker
- Dicreete and architectural installations
- Monitoring in ensambles and large filharmonic conserts mounted on microphone stands

AVALIABLE ACCESSORIES

- 19" systems DSP-amplifier with presets
- · Soft bag housing four psc. of F6X speakers and cables, for portable use, event and tour
- Quick clamp for fastening on truss, stands etc.
- Wall-mount brackets for installations
- · Microphone stand for using as nearfield monitor.
- Installation hardwares
- Compact Subwoofer for external Low frequency responce Subwoofer avaliable both passive, and active with amplifier also driving the F6X



Each hole represents 50 using the quick-release springe for fast and accurate aiming.

HX-SERIES3-WAY HORNLOADED POINT-SOURCE SPEAKERS



PRESENTATION

- ► Horn-loaded design with controled dispersion pattern
- ► Long-throw
- ► Powerful 3-way fullrange speakers
- ► Two models:

HX10: 2x10"/8"-horn/1"-horn **HX8**: 2x8"/6,5"-horn/1"-horn

- ► C.C.C. technology (Common Compression Chamber) low frequency emission.
- ► Avaliable in two versions:

Passive: 8 ohm bi-amplified with Neutrik Speakon NL4MP

Active: Self-powered with 2x1000W class-D amplifier and DSP with four presets

- ► Very high sensitivity, and low distortion levels
- ▶ Designed to be used with the B1812HPC and the B318HPC cardioid subwoofers.
- ► Can be used as groundstacked, flewn or on speaker stand
- ▶ Designed for high power live performance and installations in large nightclubs

DESIGNED FOR

- The rental and event industry
- Installations in live performance stages,
- Installations in nightclubs
- Bands and DJ's
- High power portable PA-system
- PA-companies

AVALIABLE ACCESSORIES

- 4x5200W 19" systems DSP-amplifier with presets
- Case for tour and rental, housing two pcs in each case.
- Hardwares for rigging, flying, top-hat mounting and stacking
- Installation hardwares



PRESENTATION

- Compact 2-way line array module
- ► 1 x 6,5" neodymium woofer
- ▶ 2 x 0,75" drivers mounted on waveguide and horn
- ▶ 123 dB Max SPL
- ➤ 300W cont. power handling
- ► Unique metal hardware construction
- Kick-out connection hardware with kick-release sprints
- ► H100 x V15 dispersion controled pattern
- ► Smart quick-release rigging hardware
- ► All array-hardware integrated in the inner metal construction and grille


DESIGNED FOR

- The rental and event industry
- Installations in theatres, conference centers, live performance stages, churches, audiotorium, nightclubs, sportsfacilities.
- Front-fill
- Small delay and sidefill system in larger venues and live performance events.
- Full scale compact line array for recorded music, live performance and speech.
- Delay speaker
- · Avaliable in any RAL colour upon request for dicreete and architectural installations

AVALIABLE ACCESSORIES

- 19" systems DSP-amplifier with presets
- Case for two and four modules
- Wall-mount brackets for installations
- Installation hardwares and flywares
- Ground-stack hardware for stacking on subwoofers
- Bumper frame for flying line array
- Compact 2x12" Subwoofer for extra Low frequency responce
- Active subwoofer drives subwoofer and up to eight PLA621 with 1500W + 2 x 750W
- Subwoofer for flying in array





Unique and innovative design with inner metal frame, featuring integrated hardware, connectors, passive crossover, front-grille and quick rigging array sprints.

B18HPCCARDIOID SUBWOOFER





PRESENTATION


- ► HIGH POWER CARDIOID SUBWOOFER
- ▶ 1 x 18" neodymium woofer front-loaded in tuned vented cabinet
- ▶ 1 x 12" neodymium woofer loaded in tuned vented cabinet in the back for cardioid pattern
- ▶ Advanced algorithms and acoustic design allows for very accurate cardioid responce
- ▶ Avaliable in active self-powered version, and passive bi-amplified versions
- ▶ Active version features 2 x 1500W class-D amplifiers and on-board DSP with 4 presets
- ▶ 4400W total cont. power handling
- ▶ Very high max SPL capabilities of 142 dB peak (139dB cont.)
- ▶ 103 dB sensitivity 1W/1m.
- ► Compact size for a cardioid subwoofer of only W500 x H720 x D915 mm.
- ▶ Designed for Tour, PA, portable use and installation
- Cardioid pattern with controled dispersion down to 40 Hz reduses unwanted LF on stage, and also cancels out up to 18dB behind the subwoofers
- ► In combination with the HX-series 3-way hornloaded point-source speakers the B18HPC is the perfect choice for high power medium sized live performance

DESIGNED FOR

- The rental and event industry
- Portable PA system with the HX-series horn-loaded three-way point source speakers
- High power installations in live performance stages, theatre, clubs and venues
- · Stacked and arrayed with Line array systems

AVALIABLE ACCESSORIES

- 19" systems DSP-amplifier 4 x 5200W, with presets for passive use and for installation
- Case
- Soft cover
- Castor plates and cover plates





Prophon Sound Systems and the Prophon logo are registered trademarks

Manufactured in Täby, Stockholm, Sweden by Prophon Audio & Teknik AB since 1985

Website: www.prophon.com | Mail: info@prophon.com | Tel: +46 8 92 86 00