



Constructed for medium to large cinema theaters.

The M58 was designed to satisfy the demand in a surround speaker that can handle the latest Digital Cinema sound, with low distortion, extremely high resolution and a flat response over the whole frequency range. Easy to install using any of the two the wall-mount brackets.

Fullrange frequency response, 15° angled baffle for common aiming angle. In the heart of the M58 is the sophisticated 2-way passive crossover network combined with high-end components. The M58 is designed to reproduce soundeffects, speech and music without coloring the sound, giving the audience an enjoyable and coherent sound from the surround-speakers at the sides and from the back, thus enhancing the overall cinema experience.

The baffle has an aiming angle of 15 degree for easy installations using the mounting bracket.

Technical data M48

* Power handling	350W R.M.S (700W Power handling cont.)
* Impedance	8 ohm
* Freq. Range.	50 Hz- 19 kHz (-6dB)
* Sensitivity	99 dB / 1W / 1 m
* Size / A x B x C x D x E	560 x 400 x 370 x 235 x 480 mm.
* Nominal coverage vertical	80° -6dB
* Nominal coverage horizontal	80° -6dB
* Low frequency driver	1 x 12" - woofer
* High frequency driver	1 x 1"-driver mounted on a horn
* Crossover	Passive 2-way,

